

SN 150+

Property	Unit	Test Method	Specification
Kin. Viscosity @100°C	cSt	ASTM D-7042	5.7 - 4.7
Kin. Viscosity @40°C	cSt	ASTM D-7042	TBR
Viscosity Index (Min)	-	ASTM D-2270	110
Density @15°C	kg/m ³	ASTM D-4052	TBR
Pour Point (Max)	C°	ASTM D-5950	-6
Flash Point (Min)	C°	ASTM D-92	210
Noack Volatility (Max)	wt %	ASTM D-5800	15

SN 150+

SN 150+ is a premium Group I+ base oil produced through advanced solvent refining and dewaxing. With enhanced viscosity index and thermal stability, it exceeds standard Group I specifications for high-performance lubricant formulations.

Applications

- Gasoline and marine diesel engine oils
- Bi-fuel (gasoline/LPG) and dual-fuel engine oils
- Industrial lubricants
- Grease and specialty products

Product Features

- Exceptional viscosity stability
- Light color
- Superior thermal/oxidation stability
- Low volatility
- High viscosity index (VI ≥110)
- High flash point
- Low Total Acid Number (TAN)

Packaging

- Bulk (tankers)
- Drums (208 liters)
- Flexi-tanks
- IBC Totes