

SN 150

Property	Unit	Test Method	Specification
Appearance	-	Visual	Clear & Bright
Color	-	ASTM D-1500	Max. 1.5
Density at 15°C	kg/m ³	ASTM D-4052	TBR
Kinematic Viscosity at 100°C	mm ² /s(cSt)	ASTM D-7042	6.0 - 4.7
Viscosity Index	-	ASTM D-2270	Min. 90
Flash Point	°C	ASTM D-92	Min. 210
Pour Point	°C	ASTM D-5959	Max. -6
Noack Volatility	wt %	ASTM D-5800	Max. 15

SN 150

SN 150 is a premium Group I base oil produced through solvent refining and dewaxing processes. With its light color and high viscosity index, it is widely used in formulating engine oils, industrial lubricants, and specialty products.

Applications

- Gasoline and diesel engine oils
- Bi-fuel (gasoline/LPG) and dual-fuel engine oils
- Industrial lubricants
- Grease and specialty products

Product Features

- Stable performance during operation
- Light color
- Excellent thermal and oxidation stability
- Low volatility
- Outstanding viscosity stability
- High viscosity index (VI)
- High flash point
- Low Total Acid Number (TAN)

Packaging

- Bulk (tankers)
- Flexi-tanks
- IBC Totes (1000 liters)